

BALLISTIC PERFORMANCE

Helmet Ballistic	NIJ	Frag. Velocity (17g) FSP V50		Bullets	Weight	Max Bullet Velocity	
Level	Level	m/s	ft/s	Bullets	(Grains)	m/s	ft/s
L4	IIA	520	1705	9mm FMJ RN .40 S&W 9mm CMJ RN	124 180 124	355 325 436	1165 1065 1430
L5	IIA	550	1804	9mm FMJ RN .357 Magnum JSP Plus all above bullets	124 158	400 436	1310 1430
L6	IIIA	580	1902	9mm FMJ RN .44 Magnum JSP Plus all above bullets	124 240	436 436	1430 1430
U6	IIIA	600	1968	9mm FMJ RN .44 Magnum JSP Plus all above bullets	124 240	436 436	1430 1430
M6	IIIA	620	2034	9mm FMJ RN .44 Magnum JSP Plus all above bullets	124 240	436 436	1430 1430
E6	IIIA	630	2067	9mm GECO .44 Magnum SWC-GC .357 Magnum JSP Rem Plus all above bullets	123 240 158	410 441 440	1345 1450 1445
F6	IIIA	680	2230	.44 Magnum SWC-GC .357 SIG FMJ FN 7.62 X 25 Tokarev Lead 9mm FMJ Rem* .357 GECO MP Plus all above bullets	240 125 85 124 158	441 448 450 441 390	1450 1470 555 1450 1280
F7	IIIA	735	2410	Plus all above bullets			

- *Testings NIJ 0106.01 but threats used from as per NIJ 0101.04 & NIJ 0101.06
- *Fragmentation velocities according to STANAG 2920

This helmet is the latest version of the ACH (Advanced Combat Helmet) which is very popular with Special Forces, Militaries and Law Enforcement Units due to its advanced comfort and flexibility in extreme conditions. This latest version is fitted with a 7-pad suspension system and our RD (Ratchet Dial) 4 point quick adjust harness, with the ability to take side Rails and shrouds.

The RD (Ratchet Dial) system hugely improves the rotational stability of the helmet onto the head, which is important for mounted NVG's. The operator can easily adjust the tension of the anti rotation wires by means of a dial which controls the circumferential straps of the harness from the back of the head. QA Harness: The helmets have four quick adjust buckles that make the strap tensions on the helmet easy to adjust for the wearer while the helmet is on the head. Harness Options: Leather chin strap, Plastic chin cup, Cotton chin

The shroud is manufactured from high impact composite nylon with aircraft aluminium CNC machined insert that the shroud bracket mounts onto. This insures very tight dimensional tolerances, which stabilizes the shroud. The rails are designed and manufactured from high impact composite nylon which takes a large variety of other accessories.

RAIL FITTINGS



Picatinny rails, General Purpose Mounts and Goggle Mounting Clips

OPTIONAL EXTRAS

- Neck Protector, NIJ Level IIIA
- Helmet Covers & Helmet Bags
- Helmet Velcro kit & Bungees
- Visors (Fragmentation & Ballistic) & Visor covers

COLOUR OPTIONS

Black, Navy, Olive Drab, Desert Tan, Coyote, UN Blue

HELMET SIZES

Small Medium		Large	X Large	
51 - 55 cm 54 - 59 cm		57 - 62 cm	60 - 64 cm	

FRAGMENT V50 VELOCITIES

Ballistic Lev	Fragment	Zebra Protection	Required Ballistic
	el Threats MIL	F7 Ballistic Limit	Limit as per
	STD 662	Ft/sec	standard Ft/sec
F7	2-grains RCC	4550	4200
	4-grains RCC	3475	2475
	16-grains RCC	2550	2475
	64-grains RCC	1900	1775


All products are manufactured in our own factory in Durban, South Africa with ISO9001:2015 Quality Assurance







HELMET SIZING				
Size	Circumference			
Small	51 - 55 cm			
Medium	54 - 59 cm			
Large	57 - 62 cm			
X Large	60 - 64 cm			



Measure around your head ensuring the tape passes the center of your forehead, above the ears and over the natural bump at the back of your head, allow for some tolerance.